

NCI Metal Depots Value-Plus Buildings are available in a variety of popular sizes to meet your individual needs. Value-Plus Buildings may be delivered within approximately four weeks from the time you place your order.



DESIGN, PRICE AND PURCHASE YOUR NEW  
BUILDING ONLINE AT [WWW.METALDEPOTS.COM](http://WWW.METALDEPOTS.COM)



## All Value-Plus Buildings Include:

- Bolt-together frame for easy erection
- All panels are PBR
- 26-gauge Galvalume Plus® Roof with 20-Year Warranty
- 26-gauge Painted Galvalume® walls with 20-Year Warranty
- Available in all standard colors
- Complete trim package
- All hardware, screws, closures, bolts and sealant tape as required
- Erection drawings
- Two framed openings (one per end wall)  
NOTE: These buildings are engineered for one framed opening per end wall. Additional framed openings are at the owner's risk.
- Freight, sales taxes and foundation design criteria not included

## Storage & Handling of Bundles

**NOTICE:** ALL PANEL BUNDLES MUST BE INSPECTED AND CARRIER ADVISED IMMEDIATELY IF DAMAGE IS NOTED. IF WATER IS PERMITTED TO ENTER THE BUNDLE, IT IS NECESSARY TO OPEN BUNDLE, SEPARATE MATERIAL AND DRY ALL SURFACES.

PROTECT SHEETS WHILE NESTLED IN BUNDLES:

1. Store bundled sheets off the ground sufficiently high to allow air circulation beneath bundle and to prevent rising water from entering the bundle. Slightly elevate one end of the bundle.
2. Prevent rain from entering bundle by covering with a tarpaulin, making provision for air circulation between draped edges of tarpaulin and the ground.
3. Prolonged storage of sheets in a bundle is not recommended. If conditions do not permit immediate erection, extra care should be taken to protect sheets from white rust or water marks.



www.metaldepots.com

# Value-Plus Buildings



## Load & Code Information

NCI Metal Depots also offers a variety of loading codes. Loading codes determine the maximum load a structure is designed to withstand.

Example: 20/20/110

- 20 Represents live load on frames (psf)
- 20 Represents live load on panels/purlins (psf)
- 110 Represents wind speed (mph)

### NCI METAL DEPOTS CODES

UBC	21/21/80	Exposure C	SBC	20/20/90
IBC	12/20/110		SBC	12/20/90

NCI Metal Depots provides building designs in accordance with the requirements of the latest building codes. You should select the building model that meets the Building Department requirements in your area. Buildings designed for the International Building Code (IBC) and the Standard Building Code (SBC) are designed to support a 20 psf roof live load factored and applied in accordance with the code requirements. They are designed to support wind speeds of 110 mph for IBC and 90 mph for SBC. Buildings designed for the Uniform Building Code are designed to support a 21 psf roof live load factored and applied in accordance with the code requirements, or a 30 psf ground snow load. They are designed to support wind speeds of 80 mph.

**CHECK YOUR LOCAL BUILDING CODES FOR COMPLIANCE BEFORE ORDERING YOUR NCI METAL DEPOTS BUILDING!**

## Value-Plus Buildings

SIZE	FRAMED OPENINGS*
<b>30' wide</b>	
30' x 30' x 12'	2 - 10' x 10'
30' x 40' x 10'	2 - 10' x 8'
30' x 40' x 12'	2 - 10' x 10'
30' x 40' x 14'	2 - 12' x 12'
30' x 50' x 10'	2 - 10' x 8'
30' x 50' x 12'	2 - 10' x 10'
30' x 50' x 12'	2 - 12' x 10'
30' x 50' x 14'	2 - 12' x 12'
30' x 60' x 10'	2 - 10' x 8'
30' x 60' x 12'	2 - 10' x 10'
30' x 60' x 14'	2 - 12' x 12'
30' x 75' x 12'	2 - 10' x 10'
30' x 75' x 12'	2 - 12' x 10'
30' x 75' x 14'	2 - 10' x 12'

SIZE	FRAMED OPENINGS*
<b>36' wide</b>	
36' x 36' x 12'	2 - 10' x 10'
<b>40' wide</b>	
40' x 40' x 10'	2 - 10' x 8'
40' x 40' x 12'	2 - 10' x 10'
40' x 40' x 14'	2 - 12' x 12'
40' x 50' x 10'	2 - 10' x 8'
40' x 50' x 12'	2 - 10' x 10'
40' x 50' x 14'	2 - 12' x 12'
40' x 60' x 10'	2 - 10' x 8'
40' x 60' x 12'	2 - 12' x 10'
40' x 60' x 14'	2 - 12' x 12'
40' x 60' x 14'	2 - 12' x 12'
40' x 60' x 16'	2 - 14' x 14'
40' x 75' x 10'	2 - 10' x 8'
40' x 75' x 12'	2 - 10' x 10'

SIZE	FRAMED OPENINGS*
40' x 75' x 12'	2 - 12' x 10'
40' x 75' x 14'	2 - 12' x 12'
40' x 75' x 16'	2 - 14' x 14'
40' x 80' x 12'	2 - 10' x 10'
40' x 80' x 12'	2 - 12' x 10'
40' x 80' x 14'	2 - 12' x 12'
40' x 80' x 16'	2 - 14' x 14'
40' x 100' x 12'	2 - 10' x 10'
40' x 100' x 12'	2 - 12' x 10'
40' x 100' x 14'	2 - 12' x 12'
40' x 100' x 16'	2 - 14' x 14'
<b>50' wide</b>	
50' x 50' x 10'	2 - 10' x 8'
50' x 50' x 12'	2 - 10' x 10'
50' x 50' x 12'	2 - 12' x 10'

SIZE	FRAMED OPENINGS*
50' x 50' x 14'	2 - 12' x 12'
50' x 60' x 12'	2 - 10' x 10'
50' x 60' x 12'	2 - 12' x 10'
50' x 60' x 14'	2 - 12' x 12'
50' x 75' x 12'	2 - 10' x 10'
50' x 75' x 12'	2 - 12' x 10'
50' x 75' x 14'	2 - 12' x 12'
50' x 75' x 16'	2 - 14' x 14'
50' x 80' x 12'	2 - 10' x 10'
50' x 80' x 12'	2 - 12' x 10'
50' x 80' x 14'	2 - 12' x 12'
50' x 80' x 14'	2 - 10' x 10'
50' x 80' x 12'	2 - 12' x 12'
50' x 100' x 12'	2 - 10' x 10'
50' x 100' x 14'	2 - 12' x 12'
50' x 100' x 16'	2 - 14' x 14'

SIZE	FRAMED OPENINGS*
<b>60' wide</b>	
60' x 60' x 14'	2 - 12' x 12'
60' x 75' x 14'	2 - 12' x 12'
60' x 80' x 16'	2 - 14' x 14'
60' x 100' x 12'	2 - 12' x 10'
60' x 100' x 14'	2 - 12' x 12'
60' x 100' x 16'	2 - 14' x 14'
<b>70' wide</b>	
70' x 100' x 16'	2 - 14' x 14'
<b>80' wide</b>	
80' x 100' x 16'	2 - 14' x 14'

\* One per end wall. (Doors not included.) **Note:** For 110 mph Value-Plus Buildings: Buildings rated at 110 mph are designed to be equipped with exterior doors and windows that are rated to withstand a 110 mph wind load. The use of exterior doors and windows not meeting a wind load of at least 110 mph will void all engineering.